
Smart Lock Motor GM2239E

Request a Quote
Name
WhatsApp
CAPTCHA
Submit



Smart Lock Motor GM2239F

Main Applications

Smart Door Locks

Drive for latch / bolt transmission mechanisms requiring compact packaging, low-voltage operation and repeatable opening/closing motion.

Electronic Cabinet & Locker Locks

Suitable for compact electromechanical locking mechanisms where installation space and controlled actuation are important.

Hotel / Access-Control Lock Mechanisms

Can be evaluated for lock-body actuation requiring repeated cycles and consistent low-voltage drive performance.

Customized Locking Mechanisms

For non-standard lock bodies, the motor, ratio, pinion/interface, lead wire and terminal can be evaluated against the customer's mechanism and test standard.

FAQ

Q1. How can noise be reduced in a smart lock gear motor?

Low-noise performance depends on motor speed, gear material and accuracy, gear ratio, backlash, lubrication, assembly consistency, lock-body resonance, and the control profile. For reliable evaluation, noise should be tested in the actual smart lock mechanism, including startup, running, reversing, and end-position impact, rather than relying only on no-load motor noise.

Q2. Can a smart lock motor still provide enough torque when the battery is low?

Yes, but the motor and gearbox must be selected based on the minimum operating voltage of the battery, not only the rated voltage. Low-voltage testing should simulate real conditions such as increased latch friction, door pressure, low tempera repeated unlock

Contact Us

to verify starting current, unlocking time, torque margin, and temperature rise.

Q3. How should stall or jam protection be handled in a smart lock motor system?

Stall protection should be handled by the motor, lock mechanism, and control system together. Common methods include current detection, operation timeout, end-position detection, reverse recovery, mechanical limits, and fault alarms. Peak current and stall duration should also be controlled to reduce the risk of motor overheating or mechanical damage.

Q4. How do I place an order with Shunli Motor?

Please send us your application requirements or motor specifications. Our engineering team will develop a suitable solution, confirm the technical details, and provide samples for evaluation. Once the samples are approved, we will arrange mass production. Shipping methods can be selected based on your delivery requirements.

Share:

Inquire Now

Next Product

Product Overview

Compact 4.5 VDC Smart Lock Gearmotor for Low-Speed Lock Actuation The GM2239F Smart Lock Motor is a compact 4.5 VDC DC gearmotor developed for smart door locks, electronic locks, cabinet locks, and access-control mechanisms requiring repeatable low-speed actuation. The supplied GM2239FMK267 performance data specifies 55 RPM no-load speed, 44 RPM rated speed, 40 mN·m (400 gf·cm) rated torque, and 45%–60% gearbox efficiency. Its integrated output gear, compact housing, and 26AWG wiring support embedded lock-body transmission layouts.

Model Information

Model	Motor Type	Product Category
GM2239F / GM2239FMK267	DC Brushed Gearmotor	Smart Lock / Electronic Lock Motor

Request a Quote

2.114947s

Contact Us

Main Parameters

Technical Data

Rated Voltage	4.5 VDC
Gear Ratio	Not separately specified in supplied sheet
Gearbox Efficiency	45%–60%
Max. Rated Gearbox Torque	Not specified in supplied sheet
Max. Gearbox Break Torque	Not specified in supplied sheet
Overall Height Shown	40 mm
Housing Width Shown	16 mm
Housing Depth Shown	20 mm

Technical Data

Gearmotor Model	Ratio	Voltage	No-Load Speed	No-Load Current	Rated Speed	Ra
GM2239FMK267	—	4.5 VDC	55 RPM	< 80 mA	44 RPM	< (source u label requires confirmat


Technical Data

Overall height shown	40 mm
Housing width shown	16 mm
Housing depth shown	20 mm
Output gear width shown	8 mm
Output shaft reference	Ø5 mm; Ø6 mm gear/shaft reference shown
Center interface holes shown	2 × Ø4.8 ± 0.05 mm
Lead / connector shown	1.5-2P; UL1571 / 26AWG; 240 ± 10 mm
Rotation reference	CW


Dimension Drawing

2.114947s

Contact Us




Main Applications



Industrial Automation

Industrial valves, dampers, gates, low-speed rotary platforms, adjustment mechanisms, and



Industrial Automation

Industrial valves, dampers, gates, low-sp
rotary platforms, adjustment mechanisms

Customization Range

- Electrical Configuration
- Working voltage / winding configuration, rotation direction, lead wire length and terminal options.
- Performance Matching
- Gear ratio, target output speed, rated load point, current limit and torque margin based on the real lock mechanism.
- Mechanical Interface
- Output pinion / shaft interface, mounting features and connection to the customer's lock-body transmission.
- Noise & Reliability
- Gear meshing, backlash, lubrication, motor operating point, assembly consistency and complete-lock resonance optimization.
- Control / Feedback Integration

Request a Quote

2.114947s

Hall sensor, encoder or other feedback functions can be evaluated when required by the project; availability depends on the final structure and specification.

FAQ

Applications About Us Support News

Q1: What types of projects are best suited to the GM58EM DC Worm Gear Motor?


Yes. Provide the product structure, space, load, and motion requirements, and our engineering team can assist with parameter conversion and solution evaluation.

Q2: What types of projects are best suited to the GM58EM DC Worm Gear Motor?

Q3: What types of projects are best suited to the GM58EM DC Worm Gear Motor?

Q4: What types of projects are best suited to the GM58EM DC Worm Gear Motor?


Contact Us



Related Products

Request a Quote

2.114947s



Navigation

- Home
- Customization
- Products
- Applications
- About Us
- Support
- News
- Contact Us

Product Categories

- Brushed Gear Motor
- Brushless Gear Motor
- Coreless Gear Motor
- AC Shaded Pole Gear Motor
- Smart Lock Motor

Contact Us

Tel.: +86 755 2912 4182

+86 189 2746 6971

E-mail: shunlimotor@szslmotor.com

WhatsApp: +86 18927467041

Get in Touch

* E-mail

* Message

* Submit

Copyright @ Shenzhen Shunli Motor Co., Ltd. All Rights Reserved | Powered by Reanod

Request a Quote

2.114947s