
DC Worm Gear Motor GM46EM370

PRODUCT CATEGORIES

- Brushed Gear Motor
  - Spur Gear Motor
  - Planetary Ge
  - DC Worm Gea
- Brushless Gear Motor
- Coreless Gear Motor
- AC Shaded Pole Gear Motor
- Smart Lock Motor

Contact Us



DC Worm Gear Motor GM46EM370

Main Applications

Industrial Automation

Industrial valves, dampers, gates, low-speed rotary platforms, adjustment mechanisms, and compact actuators requiring right-angle transmission.
Focus: Match starting torque, continuous torque, duty cycle, temperature rise, lubrication, and emergency manual-release requirements. Continuous high-load operation must be validated thermally.

Smart Home & Appliances

Electric doors/windows, smart blinds, smart valves, furniture adjustment, kitchen/bathroom appliances, pet equipment, and automatic opening/closing or lifting mechanisms.
Focus: Balance low noise, current consumption, motion smoothness, and holding performance. Validate frequent start/stop, reversing, long standstill, abnormal stall, and restart in the customer's actual mechanism.

Commercial & Office Equipment

Electric lifting mechanisms, vending-machine gates, smart cabinet locking/actuation, display lifting, automatic flaps, and other compact opening/closing mechanisms.
Focus: For unattended equipment, validate long-term standstill restart, humidity, lubrication aging, jam recovery, abnormal power interruption, and reverse-holding requirements.

Medical Auxiliary Equipment

Nursing-bed, medical-chair, lifting, positioning, and adjustment mechanisms where low-speed torque or right-angle transmission is needed.
Focus: Any function related to patient safety requires system-level risk control. Reverse holding must be tested, and independent mechanical locking, limit, brake, or protection mechanisms may be required.

Smart Agriculture & Gardening

Request a Quote

1.537302s

Contact Us

Ventilation/adjustment mechanisms, irrigation-related actuators, greenhouse opening/closing systems, feeding mechanisms, and equipment height or angle adjustment.

Focus: Evaluate moisture, dust, corrosion, temperature change, vibration, shock, long standstill, abnormal jam, and shaft/interface protection at the complete-product level.

AI & Service Robotics

Low-speed lifting, rotary stages, compact joints, and mechanisms that benefit from right-angle packaging and position holding.

Focus: Worm gearing has sliding friction, so battery-powered systems should calculate energy consumption and temperature rise from the real motion cycle. It may not be the best choice for high-speed or high-efficiency axes.

Automotive Electronics

Window, sunroof, seat, and other actuator concepts requiring right-angle transmission and load holding, subject to automotive-grade validation.

Focus: Anti-pinch or safety functions cannot be achieved by the gearmotor alone. Current sensing, position feedback, control logic, mechanical protection, temperature testing, vibration testing, and life validation are system responsibilities.

Application Pain Points the GM46EM370 Platform Can Address

Limited installation space: Use the 90-degree worm-drive layout to reorganize the transmission path and evaluate a shaft/interface that fits the mechanism. Insufficient starting torque or frequent stalling: Select motor platform, output speed, reduction configuration, and torque margin from starting resistance and peak-load conditions rather than from no-load speed alone. Noise, vibration, or unstable motion: Optimize gear meshing, transmission clearance, lubrication, motor load point, and installation resonance; verify the complete assembly rather than judging from the ba... Poor holding or rebound aft...g: Evaluate reverse-holding torque under real...

Request a Quote

1.537302s

Contact Us

Where safety holding is required, combine the drive with independent mechanical or control protection. Short service life under frequent cycling: Validate start/stop, reversing, overload/stall, temperature rise, bearing/gear wear, lubrication life, and long-term restart against the actual duty cycle.

FAQ

Q1: What types of projects are best suited to the GM46EM370 DC Worm Gear Motor?

It is best suited to low-speed actuator mechanisms that benefit from right-angle transmission, torque multiplication, compact packaging, and some degree of resistance to reverse driving. Typical examples include valves, gates, opening/closing mechanisms, lifting/adjustment devices, and low-speed rotary mechanisms.

Q2: Can the GM46EM370 be used as a self-locking or safety-locking drive?

Worm gearing can provide useful reverse-holding behavior in suitable configurations, but self-locking is not guaranteed for every reduction ratio, load, lubrication condition, wear state, vibration level, or temperature. For safety-critical holding, validate reverse torque and use independent mechanical or control protection where required.

Q3: How should torque and speed be selected?

Do not select only from no-load speed. Provide target speed plus continuous, starting, and peak torque, along with the transmission mechanism, installation direction, duty cycle, and maximum external load. The motor platform and reduction configuration should be matched to the complete operating point.

Q4: Is the GM46EM370 suitable for continuous operation?

Continuous operation can be evaluated, but worm gearing has sliding friction and may generate more heat than some other gear a[illegible]es. Load, current, duty cycle, a[illegible]mperature, lubrication, bearing/gear life, and [illegible]

Request a Quote

1.537302s

dissipation should be validated under the real installation condition.

Q5: What can be customized for a GM46EM370 project?

Voltage, output speed, torque matching, reduction configuration, output direction, output shaft, mounting interface, wires/terminals, rotation direction, feedback components, noise optimization, temperature-rise optimization, holding behavior, and service-life targets can be evaluated according to the project.

Q6: What information is needed for a faster quotation and engineering review?

Provide the operating voltage, target speed, continuous/starting/peak torque, installation drawing, output-shaft requirements, duty cycle, environment, noise/life target, annual demand, and certification requirements. If some data is missing, provide a sample, prototype, or mechanism drawing for initial evaluation.

Contact Us

Share:

Inquire Now

Next Product

Product Overview

The GM46 is a DC worm gear motor offering high reduction ratio, high output torque, and self-locking right-angle output. It suits smart valves, door locks, automatic curtains, vending machines, lifting devices, and industrial actuators that require compact packaging and position holding.

Model Information

Model	Motor Platform	Rated Voltage	Product Category
GM46EM370BMD018-405K	370# PMDC Motor	18 VDC	DC Worm Gear Motor

Request a Quote

Main Parameters

Technical Data

1.537302s

Gearmotor Model	Rated Voltage	No-Load Speed (RPM)	No-Load Current (mA)	Rated Speed (RPM)	Rated Current (mA)
GM46EM370BMD018-405K	18 VDC	12 ±10%	≤60	8.8 ±10%	≤200

Contact Us

Technical Data

PMDC Motor	System Voltage Reference	No-Load Speed	No-Load Current
370#	18 VDC	4000 ±10% RPM	≤40 mA


Technical Data

Product reference image - GM46EM370
Dimension / technical drawing - GM46EM370BMD018-405K

Dimension Drawing


Contact us for the dimension drawing of this model.

Main Applications



Industrial Automation

Industrial valves, dampers, gates, low-speed rotary platforms, adjustment mechanisms, and



Industrial Automation

Industrial valves, dampers, gates, low-sp rotary platforms, adjustment mechanisms

Customization Range

- Electrical Configuration

  Rated voltage, motor platform, winding configuration, rotation direction, lead wire, terminal, and connection requirements.

- Performance Matching

  Target output speed, reduction ratio, continuous/starting/peak torque, current limit, duty cycle, and operating pattern.

- Mechanical Interface

  Output direction, shaft shape and length, mounting holes/interface, bracket, bearing/sleeve selection, and gear material.

- Feedback & Functional Options

  Encoder, Hall/position feedback, limit switch, or related fu odules can be evaluated according to the control architecture.

Request a Quote

1.537302s

Noise, Thermal & Reliability Optimization

Gear meshing, lubrication, transmission clearance, temperature rise, stall/overload, reversing, long standstill restart, and target service life can be optimized and validated for the complete product.

Holding & Emergency Requirements

Reverse-holding behavior and manual-release requirements can be evaluated. Safety locking should be handled with appropriate system-level mechanical and control protection.

Contact Us

FAQ


Q1: What types of projects are best suited to the GM58EM DC Worm Gear Motor?

Yes. Provide the product structure, space, load, and motion requirements, and our engineering team can assist with parameter conversion and solution evaluation.

Q2: What types of projects are best suited to the GM58EM DC Worm Gear Motor?

Q3: What types of projects are best suited to the GM58EM DC Worm Gear Motor?

Q4: What types of projects are best suited to the GM58EM DC Worm Gear Motor?



Enable Customized Solutions to Be Implemented Faster


Whether you're in the product concept, prototype development, or mass production phase, Shunli Motors can help you find the right micro geared motor drive solution based on your specific application needs.
Submit your product requirements now and get selection advice from our engineers.

Submit Customization Requests

Request a Quote

1.537302s


Related Products



Spur gear motor GM16

We offer standard products in high, medium, and low power ranges,...


View More



Spur gear motor GM16

We offer standard products in high, medium, and low power ranges,...

View More



Spur gear motor GM16

We offer standard products in high, medium, and low power ranges,...

View More

Contact Us

Tel.: +86 755 2912 4182
+86 189 2746 6971
E-mail: shunlimotor@szslmotor.com
WhatsApp: +86 18927467041

Get in Touch

* E-mail

* Message

* HL2K Submit

Copyright @ Shenzhen Shunli Motor Co., Ltd. All Rights Reserved | Powered by Reanod

Request a Quote

HL2K

1.537302s